

View Online at <https://aerobasegroup.com/nsn/5905-00-822-3088>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.060 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.312 inches

Body Length:

0.595 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

1.50 inch-ounces

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

50.0 kilohms single section

Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:

1800.0 single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.10/+0.10 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

275.0 single section

Power Dissipation Rating Per Section In Watts:

6.9 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

4 single section

Tap Location Tolerance Per Section:

-1.0/+1.0 degrees angular rotation single section

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 single section

Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0