NSN 5905-00-822-3607

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-822-3607 **Section Quantity: Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 2.00 inch-ounces **Terminal Location:** Rear end **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 80.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 03640-6017255 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5905-00-822-3607

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0