NSN 5905-00-822-7540

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-822-7540 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.050 inches **Overall Height:** Between 0.305 inches and 0.325 inches **Overall Width:** Between 0.150 inches and 0.210 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** Between 0.115 inches and 0.135 inches **Shaft Length:** Between 0.020 inches and 0.080 inches **Body Length:** Between 0.970 inches and 1.030 inches **Body Width:** Between 0.140 inches and 0.200 inches **Body Height:** Between 0.305 inches and 0.325 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.740 inches and 0.760 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 100.0 ohms single section

Rotary Actuator Travel In Angular Deg:

5400.0

NSN 5905-00-822-7540

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure: Demilitarization:**