Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-823-3359

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.250 inches

#### Body Length:

## 0.625 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

**Screw Thread Series Designator:** 

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# **Electrical Resistance Per Section:**

500.0 kilohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# Power Dissipation Rating Per Section In Watts:

2.25 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0