NSN 5905-00-823-3504

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-823-3504 **Section Quantity:** 2 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.265 inches **Overall Height:** 0.650 inches **Overall Width:** 0.260 inches **Mounting Hole Diameter:** 0.086 inches **Body Length:** 1.265 inches **Body Width:** 0.265 inches **Body Height:** 0.650 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** Between 5760.0 and 16920.0 **Lateral Distance Between Mounting Hole Centers:** 1.015 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 500.0 ohms all sections **Rotary Actuator Travel In Angular Deg:** Between 5760.0 and 16920.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 all sections **Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

NSN 5905-00-823-3504

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 all sections
Standard Taper Curve Per Section:
A all sections
Special Features:
One separate slotted shaft for each sect, adjustment slots are flush w/case
Test Data Document:
10001-2074792 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: