Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-823-3672

Section Q	uantity:
-----------	----------

1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.875 inches **Body Diameter:** Between 0.632 inches and 0.642 inches Shaft Diameter: Between 0.151 inches and 0.161 inches Shaft Length: Between 0.469 inches and 0.531 inches

Mounting Bushing Length:

0.375 inches

**Body Length:** 

Between 0.359 inches and 0.406 inches

**Overall Diameter:** 

0.810 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

**Screw Thread Diameter:** 

0.250 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

## **Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:** 

2.0 megohms single section

**Power Dissipation Rating Per Section In Watts:** 

0.2 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0