## NSN 5905-00-823-9943

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-823-9943

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.344 inches
Flat Height:
0.219 inches
Body Diameter:
3.9375 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
2.000 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
340.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 ohms single section
Rotary Actuator Travel In Angular Deg:
340.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

## NSN 5905-00-823-9943

Demilitarization:

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 150.0 free air single section Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: --