NSN 5905-00-824-0561

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-824-0561 **Section Quantity:** First Flat Length: 0.375 inches Flat Height: 0.216 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock and at 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 200.000 percent, rated amperes c and better industrial clears **Power Dissipation Rating Per Section In Watts:** 1.0 7th secondary finish **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 3rd section **Terminal Type And Quantity:** 9 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5905-00-824-0561

Precision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0