

View Online at https://aerobasegroup.com/nsn/5905-00-824-3035

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.5620 inches

Pilot Length:

0.0620 inches

Overall Length:

2.279 inches

First Flat Length:

0.155 inches

Flat Height:

0.218 inches

Undercut Diameter:

1.825 inches

Undercut Width:

0.0780 inches

Body Diameter:

1.8438 inches

Angle Of Mounting Hole In Deg:

90.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.250 inches

Shaft Length:

0.5625 inches

Body Length:

2.0625 inches

Overall Diameter:

2.000 inches

Mounting Lip Diameter:

1.8438 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

1.250 inches

Shaft Style:

Round, flatted



| Actuator Type: |
|---|
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 3600.0 |
| Maximum Starting Torque: |
| 2.00 inch-ounces |
| Maximum Running Torque: |
| 2.00 inch-ounces |
| Screw Thread Diameter: |
| 0.164 inches |
| Screw Thread Series Designator: |
| Unc |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Mounting Facility Quantity: |
| 3 |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Threaded hole |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: |
| 1800.0 single section |
| Rotary Actuator Travel In Angular Deg: |
| 3600.0 |
| Function Conformity Tolerance Per Section: |
| -0.025/+0.025 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Fixed Tap Quantity Per Section: |
| 1 single section |
| Tap Location Tolerance Per Section: |
| -1.0/+1.0 degrees angular rotation single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| |

Continuous motion

Precision Wire Wound Variable Resistor - Page 3 of 3



Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

75.0 single section

Special Features:

Mtg holes equally spaced on 0.625 in. Mtg radius

Terminal Type And Quantity:

4 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0