NSN 5905-00-824-3036

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-824-3036
Section Quantity:
2
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.8750 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
1.917 inches
Undercut Width:
0.0700 inches
Body Diameter:
2.000 inches
Angle Of Mounting Hole In Deg:
90.0
Angle Between Centerlines Of Mounting Holes In Deg:
120.0
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Body Length:
4.109 inches
Mounting Lip Diameter:
2.0000 inches
Mounting Lip Depth:
0.0620 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
4.00 inch-ounces

4.00 inch-ounces

Maximum Running Torque:

NSN 5905-00-824-3036

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.001 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Threaded hole
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
50.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.015/+0.015 all sections
Power Dissipation Rating Per Section In Watts:
1.0 free air all sections
Function Conformity Per Section:
All sections zero based linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
75.0 all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-00-824-3036

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0