NSN 5905-00-824-7774

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-824-7774 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1243 inches and 0.1249 inches **Shaft Length:** 0.410 inches **Body Length:** 0.570 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 130.0 **Shaft End Play:** 0.005 inches **Shaft Runout:**

Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches

NSN 5905-00-824-7774

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
0.3 free air single section
Function Conformity Per Section:
Single section absolute linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-5.0/+5.0 ohms single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
500.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Test Data Document:
$97942-577r573 \ drawing, \ this is the \ basic governing \ drawing, \ such \ as \ a \ contractor \ drawing, \ original \ equipment \ manufacturer \ drawing, \ etc.;$
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-00-824-7774

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0