

View Online at <https://aerobasegroup.com/nsn/5905-00-824-9378>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.865 inches

Body Diameter:

0.880 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.500 inches

Mounting Bushing Length:

0.380 inches

Body Length:

0.370 inches

Overall Diameter:

1.130 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

310.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.359 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

320.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 heat sink single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

60.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0