NSN 5905-00-824-9719

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-824-9719

| view Online at https://derobasegroup.com/nsi//3303-00-024-37-13 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -30.0/+30.0 |
| Electrical Resistance: |
| 15.000 kilohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+275.0 |
| Inclosure Method: |
| Encased |
| Terminal Type: |
| Threaded stud |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 1.219 inches and 1.281 inches |
| Body Length: |
| Between 4.469 inches and 4.531 inches |
| Body Width: |
| Between 2.094 inches and 2.156 inches |
| Body Height: |
| Between 2.157 inches and 2.219 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 2.990 inches and 3.010 inches |
| Power Dissipation Rating In Watts: |
| 100.000 free air |
| Mounting Hole Size: |
| Between 0.178 inches and 0.188 inches |
| Style Designator: |
| Axial terminal (s) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A001a0