Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-825-1977

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# **Reliability Indicator:**

Not established

# Mounting Hole Diameter:

0.088 inches

#### Shaft Diameter:

0.110 inches

- Shaft Length:
- 0.070 inches

Body Length:

1.250 inches

## Body Width:

0.190 inches

# Body Height:

0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

7920.0

# Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

#### Terminal Location:

Rear end

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

100.000 ohms single section

# Rotary Actuator Travel In Angular Deg:

7920.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

170.0 single section

# **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

# NSN 5905-00-825-1977

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0