Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-1273

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Body Diameter:**

1.437 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

2.625 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.562 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

## Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.000 kilohms single section

# Power Dissipation Rating Per Section In Watts:

3.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

# Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0