## NSN 5905-00-826-2141

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-826-2141

Electrical Resistance: 12:100 ohms Resistance Tolerance In Percent: -1.000/-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15:0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65:0/+85.0 Inclosure Method: Hormolically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.825 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Wats: 0.500 free air Style Designator: Actal terminal each end Tests Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Tompurature Coefficient Of Resistance In Pom Per Deg Coloius
Electrical Resistance: 12.100 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.888 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-9653314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
12.100 ohms  Resistance Tolerance in Percent: -1.000/41.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0r-85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.200 inches and 0.280 inches Body Length: Between 0.200 inches and 0.843 inches Power Dissipation Rating in Watts: 0.500 free air Style Designator: Avail terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire Isaad Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Diameter: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-9363314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermeicially sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Diameter: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga63314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+85.0  Inclosure Method: Hermetically sealed  Terminal Type:  Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.898 inches and 0.843 inches  Power Dissipation Rating in Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/485.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Diameter: Between 0.220 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 64969-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  — Demilitarization: No  Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0  Inclosure Method: Hermetically sealed  Terminal Type: Wire lead Reliability Indicator: Not established  Terminal Length: Between 1.500 inches and 1.625 inches Bedy Diameter: Between 0.220 inches and 0.280 inches Body Diameter: Between 0.280 inches and 0.281 inches Between 0.688 inches and 0.843 inches Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.04-95.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 1.500 inches and 0.280 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+85.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Bedween 1.500 inches and 1.625 inches Bedween 1.500 inches and 0.280 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.88 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Diameter: Between 0.220 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.888 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.500 inches and 1.625 inches Body Diameter: Between 0.220 inches and 0.280 inches Body Length: Between 0.688 inches and 0.843 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	
Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.88 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	
Reliability Indicator: Not established  Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	
Note stablished  Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	
Terminal Length: Between 1.500 inches and 1.625 inches  Body Diameter: Between 0.220 inches and 0.280 inches  Body Length: Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator: Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Filig:	
Between 1.500 inches and 1.625 inches  Body Diameter:  Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	
Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	-
Between 0.220 inches and 0.280 inches  Body Length:  Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	
Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	
Between 0.688 inches and 0.843 inches  Power Dissipation Rating In Watts: 0.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Power Dissipation Rating In Watts:  0.500 free air  Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
O.500 free air  Style Designator:  Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
Style Designator:  Axial terminal each end  Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Axial terminal each end  Test Data Document: 64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
Test Data Document:  64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
64959-ga53314 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
Demilitarization:  No Fiig:	
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	
A001a0	
	A001a0