## NSN 5905-00-826-3401

**Section Quantity:** 

Cylindrical bushing mounted

**Body Style:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-3401

-,gg	
Reliability Indicator:	
Not established	
Overall Length:	
1.300 inches	
Body Diameter:	
Between 0.480 inches and 0.520 inches	
Shaft Diameter:	
Between 0.124 inches and 0.126 inches	
Shaft Length:	
Between 0.600 inches and 0.640 inches	
Mounting Bushing Length:	
Between 0.230 inches and 0.270 inches	
Body Length:	
Between 0.430 inches and 0.470 inches	
Overall Diameter:	
Between 0.480 inches and 0.520 inches	
Shaft Style:	
Round	
Actuator Type:	
Single shaft	
Nonturn Device Radius:	
Between 0.240 inches and 0.250 inches	
Screw Thread Diameter:	
0.250 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0	
Terminal Location:	
Rear end	
Mounting Method:	
Standard bushing	
Features Provided:	
Nonmetallic shaft	
Electrical Resistance Per Section:	
10.0 kilohms single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	

## NSN 5905-00-826-3401

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section in Percent:
-5.0/+5.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0