Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-3992

# Section Quantity:

1

Body Style: Cylindrical bushing mounted

## Reliability Indicator:

Not established

### Overall Length:

1.469 inches

#### **Body Diameter:**

Between 1.938 inches and 2.000 inches

#### Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

0.625 inches

#### Mounting Bushing Length:

Between 0.484 inches and 0.516 inches

**Body Length:** 

0.594 inches

#### **Overall Diameter:**

Between 2.203 inches and 2.266 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

Between 0.516 inches and 0.547 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Locking bushing

# **Electrical Resistance Per Section:**

2.5 megohms single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



**Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0