NSN 5905-00-826-4127

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-4127 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.960 inches **Body Diameter:** 1.160 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.380 inches **Body Length:** 1.320 inches **Overall Diameter:** 1.760 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Shaft Bearing Type:** Sleeve **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 312.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:**

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Mechanical Backlash In Deg Angular Rotation:

3.0

NSN 5905-00-826-4127

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Undercut Length: |
|--|
| 0.220 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 250.0 percent, rated amperes c and better industrial clears |
| Rotary Actuator Travel In Angular Deg: |
| 312.0 |
| Resistance Tempurature Characteristic Range Per Section In Percent: |
| +0.0/+8.0 -55 degrees celsius all sections and +0.0/+4.0 -25 degrees celsius all sections and +0.0/+2.0 0 degrees celsius all sections and |
| -3.0/+3.0 85 degrees celsius all sections and +0.0/+6.0 120 degrees celsius all sections and +0.0/+10.5 150 degrees celsius all sections |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 all sections |
| Power Dissipation Rating Per Section In Watts: |
| 3.0 free air all sections |
| Resistance Tolerance Per Section In Percent: |
| -20.0/+20.0 all sections |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 all sections |
| Standard Taper Curve Per Section: |
| A all sections |
| Special Features: |
| Inner shaft flat dimensions; 0.080 inches height; 0.220 inches length |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |