Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-4128

## Section Quantity:

2

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

2.282 inches

#### **Body Diameter:**

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

## Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

1.266 inches

## Overall Diameter:

1.484 inches

## Undercut Diameter:

0.125 inches

## Shaft Style:

Round, stepped

#### Actuator Type:

Dual concentric

## Effective Electrical Rotation In Deg Angular Rotation:

312.0

## Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

### Undercut Length:

0.250 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference



# **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 500.0 ohms c and better industrial clears **Rotary Actuator Travel In Angular Deg:** 312.0 **Resistance Tempurature Characteristic Range Per Section In Percent:** +0.0/+4.5 -55 degrees celsius 2nd section and +0.0/+2.5 -25 degrees celsius 2nd section and +0.0/+1.5 0 degrees celsius 2nd section and -1.5/+1.5 85 degrees celsius 2nd section and +0.0/+3.5 120 degrees celsius 2nd section and +0.0/+5.5 150 degrees celsius 2nd section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 all sections **Power Dissipation Rating Per Section In Watts:** 3.0 heat sink all sections **Fixed Tap Quantity Per Section:** 1 1st section **Tap Location Tolerance Per Section:** -2.0/+2.0 ohms all sections **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 all sections **Actuator Travel Control Feature:** Stops **Tap Location From Ccw Terminal Per Section In Ohms:** 2500.0 1st section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections **Standard Taper Curve Per Section:** A all sections **Terminal Type And Quantity:** 7 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0