NSN 5905-00-826-5252

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-5252

8-(

Unthreaded hole

NSN 5905-00-826-5252

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:	
0.200 inches	
Features Provided:	
Nonmetallic shaft	
Electrical Resistance Per Section:	
50.000 ohms single section	
Rotary Actuator Travel In Angular Deg:	
5400.0	
Center To Center Distance Between Center Terminal And Outside Terminal:	
0.200 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
35.0 single section	
Fempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
320.0/+320.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.5 free air single section	
Resistance Tolerance Per Section In Percent:	
10.0/+10.0 single section	
Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
25.0 single section	
Test Data Document:	
8876-202 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Ferminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Jnit Of Measure:	
-	
Demilitarization:	
No	
Filg:	
A002a0	