

View Online at <https://aerobasegroup.com/nsn/5905-00-826-6784>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.469 inches

Mounting Hole Diameter:

0.406 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.375 inches

Mounting Stud Length:

0.375 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.625 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.250 inches

Longitudinal Actuator Travel:

2.0 inches

Longitudinal Actuator Effective Electrical Stroke Length:

1.875 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Shaft locking device

Electrical Resistance Per Section:

500.000 kilohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

70.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

Single section linear

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0