## NSN 5905-00-826-9312

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-9312 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 2.160 inches **Terminal Length:** 11.500 inches **Overall Height:** Between 0.860 inches and 0.900 inches **Overall Width:** 0.313 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** Between 0.100 inches and 0.140 inches **Shaft Length:** 0.075 inches **Body Length:** 1.410 inches **Body Width:** 0.313 inches **Body Height:** Between 0.860 inches and 0.900 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 7.50 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 

**Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

**Electrical Resistance Per Section:** 

200.000 kilohms single section

## NSN 5905-00-826-9312

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: