## NSN 5905-00-826-9446

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-826-9446

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Overall Length:   |
| 0.906 inches  |
| Body Diameter:  |
| 0.781 inches  |
| Shaft Diameter:   |
| 0.125 inches  |
| Shaft Length:   |
| 0.500 inches  |
| Mounting Bushing Length:                                  |
| 0.375 inches  |
| Body Length:  |
| 0.406 inches  |
| Overall Diameter:   |
| 0.952 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Screw Thread Diameter:                                    |
| 0.250 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| Electrical Resistance Per Section:                        |
| 100.0 kilohms single section                              |
| Power Dissipation Rating Per Section In Watts:            |
| 0.2 free air single section                               |
| Resistance Tolerance Per Section In Percent:              |
| -10 0/+10 0 single section                                |

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section

## NSN 5905-00-826-9446

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0