Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-00-827-4692

Section Quantity: 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.285 inches **Terminal Length:** Between 0.173 inches and 0.203 inches **Overall Height:** 0.438 inches **Overall Width:** Between 0.155 inches and 0.185 inches Shaft Diameter: 0.078 inches Shaft Length: Between 0.025 inches and 0.045 inches **Body Length:** Between 0.230 inches and 0.270 inches **Body Width:** Between 0.155 inches and 0.185 inches **Body Height:** Between 0.230 inches and 0.270 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Terminal **Center To Center Distance Between Terminal Rows:** 0.100 inches **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 20.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3960.0



Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0