NSN 5905-00-827-6085

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-827-6085

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.220 inches
Body Diameter:
0.880 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.690 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.500 inches
Overall Diameter:
1.075 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Stop Torque:
128.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
0.290 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Screw Thread Series Designator: Unef
-
Unef

Terminal Location:

Longitudinally positioned on the circumference

NSN 5905-00-827-6085

Precision Wire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
50.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Test Data Document:
82577-955511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0