NSN 5905-00-827-7808

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-827-7808 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0150 inches **Undercut Diameter:** 4.873 inches **Undercut Width:** 0.0800 inches **Body Diameter:** 4.875 inches **Angle Of Mounting Hole In Deg: Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 2.625 inches **Mounting Lip Diameter:** 5.0000 inches **Mounting Lip Depth:** 0.0620 inches **Mounting Hole/stud Circle Diameter:** 1.750 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0

Maximum Starting Torque:

0.80 inch-ounces

NSN 5905-00-827-7808

6 turret

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Maximum Running Torque:
0.80 inch-ounces
Shaft Runout:
0.001 inches
Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.001 inches
Screw Thread Diameter:
0.164 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
3
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
6.0 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Terminal Type And Quantity:

NSN 5905-00-827-7808

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig: A002a0