Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-827-9575

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.625 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

### 0.688 inches

Shaft Style:

Round

#### Actuator Type:

Single shaft

### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

### **Mounting Method:**

Locking bushing

# **Electrical Resistance Per Section:**

50.000 ohms single section

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

# Power Dissipation Rating Per Section In Watts:

12.5 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0