Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-827-9579

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.625 inches

## Mounting Bushing Length:

0.250 inches

#### Body Length:

#### 0.688 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

### Screw Thread Diameter:

0.250 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### **Mounting Method:**

Locking bushing

#### **Electrical Resistance Per Section:**

750.000 ohms single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

## Power Dissipation Rating Per Section In Watts:

12.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0