## NSN 5905-00-827-9756

No

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-827-9756

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0/+50.0
Electrical Resistance:
100.000 ohms
Resistance Tolerance In Percent:
-10.000/+10.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
40.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+450.0
Inclosure Method:
Encapsulated
Terminal Type:
Ferrule
Reliability Indicator:
Not established
Terminal Length:
0.875 inches
Body Diameter:
1.000 inches
Body Length:
6.250 inches
Power Dissipation Rating In Watts:
125.000 free air
End Application:
Virginia class cgn (41); forrestal class cv; kidd class ddg; radar, matcs, an/tpn-22; radarsystem antps43e; over the horizen back scanne
(oth-b) program (an/fps-118); tarawa class lha; wasp class lhd; nimitz class cvn; sonar signal processing sys; an/sqq-28 (v)
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Style Designator:
Axial terminal each end
Test Data Document:
89661-128c578h02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

## NSN 5905-00-827-9756

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0