NSN 5905-00-828-0001

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-828-0001 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.512 inches **Terminal Length:** Between 0.177 inches and 0.197 inches **Body Diameter:** Between 0.490 inches and 0.510 inches **Body Length:** 0.225 inches **Overall Diameter:** Between 0.547 inches and 0.578 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Maximum Starting Torque:** 7.50 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 320.0 Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.095 inches and 0.105 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

NSN 5905-00-828-0001

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No