NSN 5905-00-828-0205

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-828-0205

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: | |
|---|-----|
| -30.0/+30.0 | |
| Electrical Resistance: | |
| 39.200 kilohms | |
| Resistance Tolerance In Percent: | |
| -1.000/+1.000 | |
| Ambient Tempurature In Deg Celsius At Full Rated Power: | |
| 25.0 | |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: | |
| 275.0 | |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: | |
| -55.0/+275.0 | |
| Inclosure Method: | |
| Encapsulated | |
| Terminal Type: | |
| Wire lead | |
| Reliability Indicator: | |
| Not established | |
| Body Diameter: | |
| 0.375 inches | |
| Body Length: | |
| 1.780 inches | |
| Power Dissipation Rating In Watts: | |
| 10.000 free air | |
| Special Features: | |
| Difference in coating specification from standard type | |
| Style Designator: | |
| Axial terminal each end | |
| Test Data Document: | |
| 97942-1ja426h79 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing | ng, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A001a0 | |