## NSN 5905-00-828-2384

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-828-2384

Tempurature Coefficient	Of Resistance I	n Ppm F	Per Deg Celsius:
-------------------------	-----------------	---------	------------------

-30.0/+30.0

**Electrical Resistance:** 

154.000 ohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0/+275.0

**Inclosure Method:** 

Encased

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

**Terminal Length:** 

Between 0.376 inches and 0.500 inches

**Body Length:** 

Between 1.876 inches and 2.000 inches

**Body Width:** 

Between 0.532 inches and 0.656 inches

**Body Height:** 

Between 0.594 inches and 0.656 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

Between 1.552 inches and 1.572 inches

**Power Dissipation Rating In Watts:** 

10.000 free air

**Terminal Width:** 

0.140 inches

**Mounting Hole Size:** 

Between 0.120 inches and 0.130 inches

Style Designator:

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39009/1 government specification

## NSN 5905-00-828-2384

Inductive Wire Wound Fixed Resistor - Page 2 of 2



S	he	lf I	Lif	e:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0