

View Online at <https://aerobasegroup.com/nsn/5905-00-828-7308>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

7.516 inches

**Body Diameter:**

3.312 inches

**Shaft Diameter:**

0.2497 inches

**Shaft Length:**

1.500 inches

**Mounting Bushing Length:**

0.438 inches

**Body Length:**

6.016 inches

**Overall Diameter:**

3.531 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

14400.0

**Maximum Starting Torque:**

3.50 inch-ounces

**Maximum Running Torque:**

2.50 inch-ounces

**Nonturn Device Location:**

At 3 oclock

**Nonturn Device Radius:**

0.531 inches

**Shaft End Play:**

0.01600 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.003 inches

**Pilot Diameter Runout:**

0.00200 inches

**Shaft Radial Play:**

0.0025 inches

**Screw Thread Diameter:**

0.500 inches

**Screw Thread Series Designator:**

Uns

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

1.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

14400.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

20.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

Single section linear

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0