Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-828-8541

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.594 inches

#### **Terminal Length:**

0.391 inches

**Body Diameter:** 

1.562 inches

Shaft Diameter:

Between 0.249 inches and 0.251 inches

### Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.375 inches

#### **Body Length:**

0.719 inches

## **Overall Diameter:**

1.953 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

285.0

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

# NSN 5905-00-828-8541

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Electrical Resistance Per Section:** 40.000 ohms single section **Rotary Actuator Travel In Angular Deg:** 295.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0