NSN 5905-00-828-8996

Section Quantity:

Terminal

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-828-8996

1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Overall Length:
0.712 inches
Terminal Length:
0.172 inches
Overall Height:
0.545 inches
Overall Width:
Between 0.180 inches and 0.230 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
0.045 inches
Body Length:
0.540 inches
Body Width:
Between 0.180 inches and 0.230 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 16220.0
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.513 inches and 0.526 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:

NSN 5905-00-828-8996

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



25.000 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0