

NSN 5905-00-828-9317 Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-828-9317 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.266 inches **Body Diameter:** Between 1.140 inches and 1.172 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** Between 0.609 inches and 0.641 inches **Mounting Bushing Length:** Between 0.234 inches and 0.266 inches **Body Length:** Between 0.593 inches and 0.625 inches **Overall Diameter:** 1.156 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:**

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

292.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.526 inches and 0.536 inches

Mechanical Backlash In Deg Angular Rotation:

1.5

Screw Thread Diameter:

0.375 inches

NSN 5905-00-828-9317

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Ferminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.5 megohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-0.0/+10.0 -55 degrees celsius single section and +0.0/+5.0 -25 degrees celsius single section and +0.0/+2.5 0 degrees celsius single
section and -3.5/+3.5 85 degrees celsius single section and +0.0/+7.5 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
20.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0