NSN 5905-00-830-6755

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-830-6755

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -50.0/+50.0 |
| Electrical Resistance: |
| 26.000 ohms |
| Resistance Tolerance In Percent: |
| -3.000/+3.000 |
| Heat Sink Material: |
| Aluminum alloy |
| Heat Sink Length: |
| 7.000 inches |
| Heat Sink Width: |
| 5.000 inches |
| Heat Sink Height: |
| 2.000 inches |
| Heat Sink Thickness: |
| 0.040 inches |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| Tomparatare Range Of Temparatare Coomolone in Bog Colonac. |
| -55.0/+275.0 |
| |
| -55.0/+275.0 |
| -55.0/+275.0 Inclosure Method: |
| -55.0/+275.0 Inclosure Method: Encased |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: |
| -55.0/+275.0 Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: 0.812 inches |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: |
| Inclosure Method: Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.375 inches Body Diameter: 0.875 inches Mounting Bushing Length: 0.783 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 12.500 free air |

Axial terminals one end

NSN 5905-00-830-6755

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0