Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-832-5237

Section Quantity:

7

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

2.8750 inches

Pilot Length:

0.0550 inches

Overall Length:

5.780 inches

Undercut Diameter:

2.875 inches

Undercut Width:

0.0600 inches

Body Diameter:

3.125 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.750 inches

Body Length:

5.000 inches

Overall Diameter:

3.364 inches

Mounting Lip Diameter:

3.0050 inches

Mounting Lip Depth:

0.0980 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

350.0

Maximum Starting Torque:

7.00 inch-ounces

Shaft Runout:

0.001 inches

Lateral Runout:

0.003 inches

NSN 5905-00-832-5237

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout	:
0.001 inches	
Terminal Location:	
	less than half the circumference
Mounting Method:	
Clamp ring	
Features Provided:	
Humidity proof	
Electrical Resistance I	
7.0 percent, rated ampo	eres c flooring
Rotary Actuator Trave	i In Angular Deg:
360.0	
Function Conformity 1	olerance Per Section:
-0.02/+0.02 all sections	
Ambient Tempurature	In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections	
Tempurature Coefficie	ent Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 all section	ıs
Power Dissipation Rat	ing Per Section In Watts:
4.0 free air all sections	
Function Conformity F	er Section:
All sections absolute co	nformity
Fixed Tap Quantity Pe	r Section:
3 3rd section	
Resistance Tolerance	Per Section In Percent:
-20.0/+20.0 2nd section	
Actuator Travel Contro	ol Feature:
Continuous motion	
Function Characterist	c Per Section:
All sections table	
Ambient Tempurature	In Deg Celsius Per Section At Full Rated Power:
25.0 all sections	
Test Data Document:	
19200-10545461 drawir	ng (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any spec	ification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Qu	antity:
27 turret	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	