

View Online at <https://aerobasegroup.com/nsn/5905-00-832-5904>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Overall Length:

Between 1.234 inches and 1.266 inches

Terminal Length:

Between 0.340 inches and 0.350 inches

Overall Height:

Between 0.359 inches and 0.391 inches

Overall Width:

Between 0.296 inches and 0.328 inches

Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

Body Length:

Between 1.234 inches and 1.266 inches

Body Width:

Between 0.296 inches and 0.328 inches

Body Height:

Between 0.359 inches and 0.391 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

Between 11520.0 and 13680.0

Maximum Starting Torque:

6.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

500.000 ohms single section

Rotary Actuator Travel In Angular Deg:

Between 11520.0 and 13680.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Terminal pin 0.030 in. Diameter porm 0.005 in, terminals gold plated

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0