

View Online at <https://aerobasegroup.com/nsn/5905-00-833-2702>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Overall Length:

Between 1.296 inches and 1.328 inches

Terminal Length:

Between 0.484 inches and 0.516 inches

Overall Height:

Between 0.780 inches and 0.844 inches

Overall Width:

Between 0.234 inches and 0.266 inches

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

Between 0.109 inches and 0.141 inches

Shaft Length:

Between 0.046 inches and 0.078 inches

Body Length:

Between 1.234 inches and 1.266 inches

Body Width:

Between 0.234 inches and 0.266 inches

Body Height:

Between 0.296 inches and 0.328 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

Between 0.690 inches and 0.710 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.109 inches and 0.141 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Grounded contact arm

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.290 inches and 0.310 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0