Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-833-3082

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.250 inches

#### Shaft Diameter:

0.249 inches

Shaft Length:

Between 2.969 inches and 3.031 inches

#### Mounting Bushing Length:

0.375 inches

#### Body Length:

0.719 inches

# Shaft Style:

Round

## Actuator Type:

Single shaft

#### Nonturn Device Location:

At 3 oclock and at 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Fragility Factor:

Moderately rugged

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

50.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0