NSN 5905-00-833-4292



Nonprecision Wire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-00-833-4292 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.050 inches **Body Length:** 1.000 inches **Body Width:** 0.180 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft

Olligic Shart

Effective Electrical Rotation In Deg Angular Rotation:

5400.0

Lateral Distance Between Mounting Hole Centers:

0.750 inches

Mounting Facility Quantity:

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

5400.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

NSN 5905-00-833-4292

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: