NSN 5905-00-833-4627

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-833-4627

Electrical Resistance: 75 000 ohms Resistance Tolerance In Percent: -0.020/4/0.020 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.250 inches Body Length: -0.750 inches Power Dissipation Rating In Watts: -0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: -0.020/4-0.020 Ambient Tempurature in Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -145.0 -1	-15.0/+15.0
Resistance Tolerance In Percent: -0.020/+0.020 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axida terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure: — Demilitarization: No Filig:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Avial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	75.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	-0.020/+0.020
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: No Unit of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/A Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-55.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Terminal Type:
Note stablished Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Length: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Not established
Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
0.750 inches Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Power Dissipation Rating In Watts: 0.250 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Oriticality Code Justification: Test Style Designator: Axial terminal each end Test Dota Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 inches
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Style Designator: Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Axial terminal each end Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test
Test Data Document: 11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	11293-36-268701 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a Unit Of Measure: Demilitarization: No Filig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0