## NSN 5905-00-833-7657

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-833-7657 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 0.880 inches **Terminal Length:** 0.156 inches **Overall Height:** Between 0.466 inches and 0.471 inches **Overall Width:** Between 0.090 inches and 0.110 inches **Shaft Diameter:** Between 0.090 inches and 0.110 inches **Shaft Length:** 0.130 inches **Body Length:** 0.750 inches **Body Width:** 0.160 inches **Body Height:** 0.310 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7200.0 **Center To Center Distance Between Terminals:** 0.500 inches **Fragility Factor:** Moderately delicate **Lateral Distance Between Mounting Hole Centers:** 0.375 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method:** 

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

## NSN 5905-00-833-7657

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Cubic Measure:
0.0372 cubic inches
Electrical Resistance Per Section:
500.000 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
7200.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A002a0