## NSN 5905-00-834-0534

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-834-0534 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.880 inches **Terminal Length:** 0.156 inches **Overall Height:** 0.466 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.130 inches **Body Length:** 0.750 inches **Body Width:** 0.160 inches **Body Height:** 0.310 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7200.0 **Center To Center Distance Between Terminals:** 0.500 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.100 inches **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg: 7200.0

## NSN 5905-00-834-0534

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.200 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No