Nonprecision Wire Wound Variable Resistor - Page 1 of 2



334-1153

View Online at https://aerobasegroup.com/nsn/5905-00-83
Section Quantity:
1
Reliability Indicator:
Not established
First Flat Length:
1.562 inches
Flat Height:
0.344 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.000 inches
Shaft Style:
Round, flatted
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Single shaft
Lateral Distance Between Mounting Hole Centers:
1.750 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Mounting Facility Quantity:
2
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
11.000 ohms single section
Power Dissipation Rating Per Section In Watts:
225.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0