NSN 5905-00-834-1756

Non-wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-834-1756 **Section Quantity: Body Style:** Cylindrical bushing mounted **Overall Length:** 1.219 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.469 inches **Overall Diameter:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 295.0 **Nonturn Device Location:** At 10'30 oclock **Nonturn Device Radius:** 0.245 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft

Rotary Actuator Travel In Angular Deg:

295.0

NSN 5905-00-834-1756

Non-wire Wound Variable Resistor - Page 2 of 2



	Ambient Tempurature	e In Deg Celsius	Per Section At Zero	Percent Rated Power:
--	---------------------	------------------	---------------------	----------------------

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

•...•... **=**...

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0