Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-834-3427

Section Quantity:
1
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Shaft Style:
Round
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Contact Arm Electrical Off Position:
Fully cw
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.547 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
6.000 ohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Switch Current Type And Rating In Amps:
3.000 ac/dc

## NSN 5905-00-834-3427

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Standard Taper Curve Per Section:

A single section

## **Special Features:**

Switch closes before resistor circuit is closed 300.0 degrees porm 5.0 pct. Rotation

## Terminal Type And Quantity:

3 tab, solder lug and 2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0