NSN 5905-00-834-3427

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-834-3427 **Section Quantity: Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Shaft Style:** Round Switch Type: Rotary Switch Voltage Rating In Volts: 125.0 **Contact Arm Electrical Off Position:** Fully cw **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.547 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Features Provided:** Switch **Electrical Resistance Per Section:** 6.000 ohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Switch Current Type And Rating In Amps:

3.000 ac/dc

NSN 5905-00-834-3427

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Special Features:
Switch closes before resistor circuit is closed 300.0 degrees porm 5.0 pct. Rotation
Terminal Type And Quantity:
3 tab, solder lug and 2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No